LANYARDS

AK ABM LB102/1

DOUBLE LANYARD

PRODUCT SPECIFICATIONS

- Double rope 2m with 2 extra large alu scaffold hooks (opening 60mm) & 1 twist lock steel carabiner
- Double lanyard is a component of personal protective equipment against falls from a height and complies with EN354. The lanyard LB 102 is made of ø10.5mm polyamide kernmantle rope. The ends of the lanyard are sewn making the connecting loops equipped with thimbles.
- Energy absorbers are a component of personal protection equipment. It is made from polyester webbing. Energy absorber made of 32 mm wide polyamide webbing. Absorber is equipped with attaching loops on the endings. The body of the absorber is protected by special jacket made of a shrinkable, polyethylene tube.



- Maximal elongation of the energy absorber: ~1.20 m.
- The double lanyard without the energy absorber is not a fall protection.
- Made in EUROPE

PRODUCT USE



CONSTRUCTION / CIVIL ENGINEERING



HEAVY INDUSTRY



LIGHT INDUSTRY



OIL / GAS

PRODUCT RISKS



WEAR & TEAR

CERTIFICATIONS AND STANDARDS

C € 0082 THE ENERGY ABSORBER IS A COMPONENT OF PERSONAL FALL ARREST EQUIPMENT AND COMPLIES WITH EN355.

EN 354:2002

EN 355:2002 FALL ARREST SYSTEM CONSISTED OF ENERGY ABSORBER (COMPLIED WITH EN 355)

CONNECTED TO LANYARD (COMPLIED WITH EN 354)

- THE MAXIMUM LIFETIME OF OUR PRODUCTS IS 10 YEARS FROM THE DATE OF MANUFACTURE THE MAX<mark>IMUM TIME</mark> OF USE OF OUR PRODUCTS IS 5 YEARS FROM THE DATE OF FIRST USE
- THE PERIODIC INSPECTION MUST BE CARRIED OUT AT LEAST ONCE EVERY 12 MONTHS OF USE
- THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT HAS BEEN SUBJECTED TO A MAJOR FALL
- THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT FAILS TO PASS INSPECTION.

- IT'S RESTRICTED TO USE THE EQUIPMENT WITHOUT MARKING AND WITHOUT VALID IDENTITY CARD

AKROBAT PTE LTD

53 Ubi Avenue 1 #05-13 Paya Ubi Industrial Park Singapore 408934 Tel: 6744 4235 Fax: 6333 8836

salesup@akrobat.com.sg / www.akrobat.com.sg















