



The Height Safety Specialist

www.akrobat.com.sg

LANYARDS

AK FS531

TUFF LANYARD

PRODUCT SPECIFICATIONS

- Energy absorber pack
- 44mm webbing PES Biothane®, 25KN
- High strength polyester stitches thread no. 10 >180N
- 60mm opening aluminium large hook, double locking
- 20mm opening aluminium karabiner, double locking
- Length 2m with the hook and carabiner
- Weight 1.5 Kg

PRODUCT'S HIGHLIGHTS & USER'S BENEFITS

- Designed for dirty jobs such as oil field work, offshore, roofing, painting and food industry
- Easy to clean after work as webbing protected by layer of PES
- Made in EUROPE

PRODUCT USE



CONSTRUCTION / CIVIL ENGINEERING



HEAVY INDUSTRY



LIGHT INDUSTRY



OIL / GAS

PRODUCT RISKS



WEAR & TEAR

CERTIFICATIONS AND STANDARDS

CE EN354 EN355



NOTES:

- THE MAXIMUM LIFETIME OF OUR PRODUCTS IS 10 YEARS FROM THE DATE OF MANUFACTURE
- THE MAXIMUM TIME OF USE OF OUR PRODUCTS IS 5 YEARS FROM THE DATE OF FIRST USE
- THE PERIODIC INSPECTION MUST BE CARRIED OUT AT LEAST ONCE EVERY 12 MONTHS OF USE
- THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT HAS BEEN SUBJECTED TO A MAJOR FALL
- THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT FAILS TO PASS INSPECTION
- IT'S RESTRICTED TO USE THE EQUIPMENT WITHOUT MARKING AND WITHOUT VALID IDENTITY CARD

AKROBAT PTE LTD

53 Ubi Avenue 1 #05-13 Paya Ubi Industrial Park Singapore 408934

Tel : 6744 4235 Fax : 6333 8836

salesup@akrobat.com.sg / www.akrobat.com.sg

