



The Height Safety Specialist

www.akrobat.com.sg

ROPES

AKKC4003

SEMI-STATIC ROPES Ø11 MM

PRODUCT SPECIFICATIONS

- Multiple twisted nylon cores , 200 meters
- 16 plait nylon cover
- Ave. strength: 21.1 kN
- Weight / metre : 73.8g/m
- Colour: AKKC4003- White with tracer
- Rope Classification A
- 50 - 150 kg Elongation (2.4%)
- Shrinkage (4%)
- Minimum Static Strength ex. terminations (22kN)
- Average Static Strength ex. terminations (35.3kN)
- Average Static Strength with fig. 8 loop (21.1kN)
- Fall Factor 1 falls. fig. 8 loop - 10+
- Peak Force (kN) fig. 8 loop - 5.8



PRODUCT'S HIGHLIGHTS & USER'S BENEFITS

- A static ropes that are designed for rope access, line rescue, controlled descent and for use in speleology..
- Low Stretch Kernmantle polyamide ropes are available with a performance enhancing coating that has 3 main benefits:
 - 1) The reduction of water absorption.
 - 2) Improved resistance to abrasion damage.
 - 3) Resistance to ingress of foreign matter such as sand and mud.
- Made in Europe

PRODUCT USE



CONSTRUCTION / CIVIL ENGINEERING



FALL PREVENTION



SECOND WORK / CRAFTMAN



LIGHT INDUSTRY



HEAVY INDUSTRY



AGRICULTURE/GREEN AREAS



OIL / GAS



WIND ENERGY



MINING



SERVICES / LOGISTICS



CERTIFICATIONS AND STANDARDS

CE

PPE DIRECTIVE 89/686/EEC

EN1891:1998

Classification Type A

AKROBAT PTE LTD

53 Ubi Avenue 1 #05-13 Paya Ubi Industrial Park Singapore 408934

Tel : 6744 4235 Fax : 6333 8836

salesup@akrobat.com.sg / www.akrobat.com.sg

